

## **Polaris Series | PPS-1050FC**

- 80 PLUS® Gold certified efficiency
- Fully modular cable management
- LLC Half-bridge converter with DC-to-DC technology

The Polaris Series brings CHIEFTEC's trusted and proven experience with high quality, 80 PLUS® Gold certified, fully modular power supplies back to the forefront of modern technology. Polaris Series PSU's feature state-of-the-art technical design including LLC half-bridge converter with DC-to-DC technology, as well as high power-density to allow higher efficiency and power output with a more compact size. Cable lengths of 650mm ensure that these power-supplies can be used even in large builds.





Technical data				
Model	Polaris Series			
Articel no.	PPS-1050FC			
ATX12V Version	v 2.53			
Efficiency	80 PLUS® Gold			
PFC	Active PFC			
Fan	135mm FDB silent fan			
Dimension (DxWxH)	160mm x 150mm x 86mm			
Security	AFC (Automatic Fan speed Control) OCP (Over Current Protection) OPP (Over Power Protection) OTP (Over Temperature Protection) OVP (Over Voltage Protection) SCP (Short Circuit Protection) SIP (Surge & Inrush Protection) UVP (Under Voltage Protection)			
Warranty	24 Months			

Output data								
	AC Input	100-240V / 15 - 8A / 50 - 60Hz						
PPS - 1050FC	DC Output	+3.3V	+5V	+12V	-12V	+5VSB		
	Max. Current	22A	22A	87.5A	0.3A	3.0A		
	Max. Combined Power	120W		1050W	3.6W	15W		
		1050W						

<sup>\*</sup> The listed specifications may be altered at any point in time without any pre-notice.

<sup>\*\*</sup> Chieftec\* is a registered trademark. All other brands and/or logos are property of the respective owners.



## **Polaris Series | PPS-1050FC**

Cable	Connectors	Length (mm)
24 PIN ATX	1	650
8 PIN EPS (4+4)	2	2 x 650
8 PIN PCIe (6+2)	6	3 x 600/100
SATA	12	3 x 550/100/100/100
MOLEX	4	550/100/100/100



Version: 10/2020

<sup>\*</sup> The listed specifications may be altered at any point in time without any pre-notice.

<sup>\*\*</sup> Chieftec\* is a registered trademark. All other brands and/or logos are property of the respective owners.