

PRODUCT DATASHEET

LS AY PFM -CP/P2/500/P

LED STRIP VALUE-300 PROTECTED | IP65 protected LED strips with 300 lm/m for general applications

Areas of application

- General indoor illumination



Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	0...36 V
Nominal current	5000 mA

Dimensions & weight

Length	552 mm
Cable length	500 mm
Width	15,0 mm
Height	7 mm
Product weight	11.00 g

Colors & materials

Product color	Transparent
---------------	-------------

Temperatures & operating conditions

Ambient temperature range	-15...+45 °C
Temperature range in operation	-15...+45 °C



Certificates & standards

Type of protection	IP66
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-35...+85 °C
------------------------------	--------------

DOWNLOAD DATA

DOWNLOAD DATA	
	Certificates EAEC N RU D-DE.MYu62.B.01040 20 13.03.2020-12.03.2025
	Catalogs LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075272958	BAG 2	80 mm x 120 mm x 5 mm	23.00 g	0.05 dm ³
4058075272965	Shipping box 100	180 mm x 100 mm x 180 mm	1229.00 g	3.24 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075272972	SHIPPING BOX FOR 5TH-LEVEL 1,000	520 mm x 380 mm x 210 mm	13057.00 g	41.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.