

PRODUCT FAMILY DATASHEET

SMART+ WiFi Candle Multicolour

Classic candle shape with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h



TECHNICAL DATA

Electrical data

Product description	Nominal wattage	Construction wattage	Nominal voltage	Nominal current	Operating frequency
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	4.9 W	4.90 W	230 V	45 mA	50...60 Hz
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	4.9 W	4.90 W	230 V	45 mA	50...60 Hz

Product description	Mains frequency	Power factor λ	Claimed equiv. conventional lamp power
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	50...60 Hz	> 0.5	40 W
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	50...60 Hz	> 0.50	40 W

Photometrical data

Product description	Light color (designation)	Lumen main.fact.at end of nom.life time	Standard deviation of color matching	Nominal luminous flux	Luminous flux
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	RGBW	0.70	≤ 6 sdc _m	470 lm	470 lm
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	RGBW	0.70	≤ 6 sdc _m	470 lm	470 lm

Product description	Luminous efficacy	Adjustable color temperature	Color temperature	Color rendering index Ra	Flickering metric (Pst LM)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	95 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	95 lm/W	2700...6500 K	2700...6500 K	80	1.0

Product description	Stroboscope effect metric (SVM)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.9
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.9

Light technical data

Product description	Beam angle	Starting time
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	SPHERE_360	< 0.5 s
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	200 °	

Dimensions & Weight

Product description	Product weight	Diameter	Length	Width (incl. round luminaires)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	32.00 g	37.50 mm	107.00 mm	37.50 mm
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	32.00 g	37.50 mm	107.00 mm	37.50 mm

Product description	Height (incl. round luminaires)	Outer bulb [PICOS]
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	37.50 mm	B40
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	37.50 mm	B40

Lifespan

Product description	Nominal lamp life time	Lumen maintenance at end of serv
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	20000 h	0.70
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	20000 h	0.70

Colors & materials

Product description	Housing color
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	White
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	White

Temperatures & operating conditions

Product description	Ambient temperature range
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	-20...+40 °C
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	-20...+40 °C

Additional product data

Product description	Mercury-free	Product remark	Base (standard designation)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E14

Product description	Mercury-free	Product remark	Base (standard designation)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E14

Capabilities

Product description	Dimmable	Compatible smart home technology
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	Yes	Google Assistant / Amazon Alexa
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	Yes	Google Assistant / Amazon Alexa

Certificates & Standards

Product description	Energy efficiency class	Energy consumption	Standards	Type of protection
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	F ¹⁾	5.00 kWh/1000h	CE	IP20
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	F ¹⁾	5.00 kWh/1000h	CE	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Product description	Lighting technology used	Non-directional or directional	Mains or non-mains	Light source cap-type (or other electric interface)	Connected light source (CLS)
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	LED	NDLS	MLS	E14	yes
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	LED	NDLS	MLS	E14	yes

Product description	Color-tuneable light source	Envelope	High luminance light source	Anti-glare shield	Correlated colour temperature type
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	yes	No	No	No	RANGE
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	yes	No	No	No	RANGE

Product description	Standby power	Networked standby power for CLS	Claim of equivalent power	Chromaticity coordinate x	Chromaticity coordinate y
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.50	0.50	Yes	0.463	0.420

Product description	Standby power	Networked standby power for CLS	Claim of equivalent power	Chromaticity coordinate x	Chromaticity coordinate y
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.50	0.50	Yes	0.463	0.420

Product description	R9 Colour rendering index	Beam angle	Survival factor	Displacement factor	LED light source replaces a fluorescent light source
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	0.00	SPHERE_360	0,9	0.50	not applicable

Product description	EPREL ID	Model number
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	528208	AC33921
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	528208,528208	AC33921,AC33921

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.



SALES AND TECHNICAL SUPPORT

Sales and Technical Support www.ledvance.com

COUNTRY SPECIFIC INFORMATION

Product description	Product code	METEL-Code	SEG number	STK number	UK Org
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	4058075485570	-	8296154	4736614	-
SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14	4058075485938	-	-	-	-

DOWNLOAD DATA

DOWNLOAD DATA	
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Installation guide SMART+ WIFI INSTALLATION GUIDE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485570	Folding box 1	61 mm x 96 mm x 154 mm	103.00 g	0.90 dm ³
4058075485938	Folding box 3	67 mm x 130 mm x 204 mm	245.00 g	1.78 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.