

PRODUCT FAMILY DATASHEET

SMART+ WiFi Classic Multicolour

Classic bulb shape with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 15,000 h



TECHNICAL DATA

Electrical data

Product description	Nominal wattage	Construction wattage	Nominal voltage	Nominal current	Operating frequency
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	9 W	9.00 W	230 V	52 mA	50...60 Hz
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	9 W	9.00 W	230 V	52 mA	50...60 Hz
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	9 W	9.00 W	230 V	52 mA	50...60 Hz
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	9 W	9.00 W	230 V	52 mA	50...60 Hz
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	9 W	9.00 W	230 V	52 mA	50...60 Hz
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	9.5 W	9.50 W	230 V	68 mA	50...60 Hz
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	9.5 W	9.50 W	230 V	68 mA	50...60 Hz
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	14 W	14.00 W	230 V	70 mA	50...60 Hz
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	14 W	14.00 W	230 V	70 mA	50...60 Hz

Product description	Mains frequency	Power factor λ	Claimed equiv. conventional lamp power
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50...60 Hz	> 0.5	60 W
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50...60 Hz	> 0.5	60 W
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50...60 Hz	> 0.5	60 W
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	50...60 Hz	> 0.5	60 W
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	50...60 Hz	> 0.5	60 W
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	50...60 Hz	> 0.5	75 W
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	50...60 Hz	> 0.5	75 W
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	50...60 Hz	> 0.5	100 W
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	50...60 Hz	> 0.5	100 W

Photometrical data

Product description	Light color (designation)	Lumen main.fact.at end of nom.life time	Standard deviation of color matching	Nominal luminous flux	Luminous flux
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	806 lm	806 lm
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	806 lm	806 lm
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	806 lm	806 lm
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	RGBW	0.70	≤6 sdc _m	806 lm	806 lm
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	RGBW	0.70	≤6 sdc _m	806 lm	806 lm
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	1055 lm	1055 lm
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	1055 lm	1055 lm
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	1521 lm	1521 lm
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	RGBW	0.70	≤6 sdc _m	1521 lm	1521 lm

Product description	Luminous efficacy	Adjustable color temperature	Color temperature	Color rendering index Ra	Flickering metric (Pst LM)
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	89 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	89 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	89 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	89 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	89 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	111 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	111 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	108 lm/W	2700...6500 K	2700...6500 K	80	1.0
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	108 lm/W	2700...6500 K	2700...6500 K	80	1.0

Product description	Stroboscope effect metric (SVM)
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.9
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.9
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.9
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.9

Light technical data

Product description	Beam angle	Starting time
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	SPHERE_360	< 0.5 s
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	215 °	
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	215 °	
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	215 °	
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	215 °	
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	215 °	
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	215 °	< 0.5 s
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	215 °	< 0.5 s
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	215 °	

Dimensions & Weight

Product description	Product weight	Diameter	Length	Width (incl. round luminaires)	Height (incl. round luminaires)
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50.00 g	60.00 mm	111.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50.00 g	60.00 mm	111.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	50.00 g	60.00 mm	111.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	50.00 g	60.00 mm	111.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	50.00 g	60.00 mm	111.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	50.00 g	60.00 mm	115.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	50.00 g	60.00 mm	115.00 mm	60.00 mm	60.00 mm
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	100.00 g	75.00 mm	141.50 mm	75.00 mm	75.00 mm
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	100.00 g	75.00 mm	141.50 mm	75.00 mm	75.00 mm

Product description	Outer bulb [PICOS]
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	A60
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	A60
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	A60
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	A60
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	A60
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	A60
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	A60
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	A75
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	A75

Lifespan

Product description	Nominal lamp life time	Lumen maintenance at end of serv
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	15000 h	
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	15000 h	
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	15000 h	0.70
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	15000 h	0.70

Colors & materials

Product description	Housing color
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	White
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	White
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	White
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	White
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	White
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	White
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	White

Temperatures & operating conditions



Product description	Ambient temperature range
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	-20...+40 °C
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	-20...+40 °C
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	-20...+40 °C
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	-20...+40 °C

Additional product data

Product description	Mercury-free	Product remark	Base (standard designation)
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	B22d



Product description	Mercury-free	Product remark	Base (standard designation)
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	B22d
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	Yes	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	E27

Capabilities

Product description	Dimmable	Compatible smart home technology
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	Yes	Amazon Alexa / Google Assistant
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	Yes	Amazon Alexa / Google Assistant
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	Yes	Amazon Alexa / Google Assistant
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa



Product description	Dimmable	Compatible smart home technology
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	Yes	Google Assistant / Amazon Alexa

Certificates & Standards

Product description	Energy efficiency class	Energy consumption	Standards	Type of protection
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	F ¹⁾	9.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	F ¹⁾	9.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	F ¹⁾	9.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	F ¹⁾	9.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	F ¹⁾	9.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	F ¹⁾	10.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	F ¹⁾	10.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	F ¹⁾	14.00 kWh/1000h	CE	IP20
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	F ¹⁾	14.00 kWh/1000h	CE	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Product description	Lighting technology used	Non-directional or directional	Mains or non-mains	Light source cap-type (or other electric interface)	Connected light source (CLS)
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	LED	NDLS	MLS	B22d	yes
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	LED	NDLS	MLS	B22d	yes
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes



Product description	Lighting technology used	Non-directional or directional	Mains or non-mains	Light source cap-type (or other electric interface)	Connected light source (CLS)
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	LED	NDLS	MLS	E27	yes

Product description	Color-tuneable light source	Envelope	High luminance light source	Anti-glare shield	Correlated colour temperature type
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	yes	No	No	No	RANGE
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	yes	No	No	No	RANGE
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	yes	No	No	No	RANGE
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	yes	No	No	No	RANGE

Product description	Standby power	Networked standby power for CLS	Claim of equivalent power	Chromaticity coordinate x	Chromaticity coordinate y
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.50	0.50	Yes	0.463	0.420



Product description	Standby power	Networked standby power for CLS	Claim of equivalent power	Chromaticity coordinate x	Chromaticity coordinate y
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.50	0.50	Yes	0.463	0.420

Product description	R9 Colour rendering index	Beam angle	Survival factor	Displacement factor	LED light source replaces a fluorescent light source
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.50	not applicable
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.70	not applicable
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	0.00	SPHERE_360	0,9	0.70	not applicable

Product description	EPREL ID	Model number
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	528198,528198	AC33911,AC33911
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	528198,528198	AC33911,AC33911
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	528198	AC33911
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	528199,528199	AC33912,AC33912
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	528199	AC33912



Product description	EPREL ID	Model number
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	528202,528202	AC33915,AC33915
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	528202	AC33915
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	528205,528205	AC33918,AC33918
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	528205,528205	AC33918,AC33918

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.




SALES AND TECHNICAL SUPPORT

Sales and Technical Support www.ledvance.com

COUNTRY SPECIFIC INFORMATION

Product description	Product code	METEL-Code	SEG number	STK number	UK Org
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	4058075485396	-	8296151	4736610	-
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	4058075485754	-	8296162	4736611	-
SMART+ WiFi Classic 60 9 W/2700...6500 K E27	4058075521438	-	-	-	-
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	4058075521414	-	-	-	-
SMART+ WiFi Classic 60 9 W/2700...6500 K B22d	4058075515680	-	-	-	-
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	4058075485815	-	-	-	-
SMART+ WiFi Classic 75 9.5 W/2700...6500 K E27	4058075485457	-	-	-	-
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	4058075485518	-	-	4736612	-
SMART+ WiFi Classic 100 14 W/2700...6500 K E27	4058075485877	-	-	4736613	-

DOWNLOAD DATA

DOWNLOAD DATA	
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity

DOWNLOAD DATA

	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE
	Declarations of conformity
	Installation guide SMART+ WIFI INSTALLATION GUIDE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485396	Folding box 1	61 mm x 96 mm x 154 mm	124.00 g	0.90 dm ³



Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485754	Folding box 3	67 mm x 130 mm x 204 mm	317.00 g	1.78 dm ³
4058075521438	Folding box 2	96 mm x 154 mm x 61 mm	130.00 g	0.90 dm ³
4058075521414	Folding box 1	61 mm x 96 mm x 154 mm	124.00 g	0.90 dm ³
4058075515680	Folding box 3	67 mm x 130 mm x 204 mm	317.00 g	1.78 dm ³
4058075485815	Folding box 3	67 mm x 130 mm x 204 mm	317.00 g	1.78 dm ³
4058075485457	Folding box 1	61 mm x 96 mm x 154 mm	124.00 g	0.90 dm ³
4058075485518	Folding box 1	79 mm x 96 mm x 154 mm	201.00 g	1.17 dm ³
4058075485877	Folding box 3	82 mm x 150 mm x 247 mm	481.00 g	3.04 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

