## BHI611ES



## Integrated



LedLight

Re-circulating hoods



Noise level

Integrated into the cabinet Venting with air extraction or recirculation Energy class: **D** Material of housing/chimney: **varnished steel** Colour of housing/chimney: **grey** Lightning efficiency class: **C** 

Grease filtering efficiency class: **D** Fluid dynamic efficiency class: **E** Maximum extraction rate by extraction operation: **370 m<sup>3</sup>/h** Maximum extraction rate by recirculation operation: **140 m<sup>3</sup>/h** Venting tube diameter: **12 cm** 

Air flow by extraction version, step 1: **290 m<sup>3</sup>/h** Air flow by extraction version, step 2: **340 m<sup>3</sup>/h** Air flow by extraction version, step 3: **370 m<sup>3</sup>/h** 

Mechanic control Control setting: **Switch** Number of speed positions: **3** 

Lamp type: **LED** On/off light switch Number of lights: **2** Power of lights: **6 W** 

Filter material: **Aluminium** Coal filter code (optional as separate purchase): **416912** Number of filters: **1** Washable grease filter Number of motors: **1** 

Max. noise level: **67 dB(A)re 1 pW** Height: **208 mm** Annual energy consumption: **70.7 kWh** Dimensions (W×H×D): **53.4 × 20.8 × 30 cm** Dimensions of packed product (W×H×D): **58 × 24 × 32.4 cm** Net weight: **4.8 kg** Gross weight: **5.9 kg** Connected load: **146 W** Product code: **733140** EAN code: **3838782176388** 

