



# Essential Smartbright Bulkhead

## WT045C LED20/NW PSU CFW L1665

Power supply unit - Polycarbonate bowl/cover - 100° x 120°

The new essential smartbright bulkhead is great value for money. It is IP65 waterproof design and comes in 2 sizes based on your specific lighting needs.

### **Product data**

General Information		
Beam angle of light source	120 °	
Light source color	740 neutral white	
Number of gear units	1 unit	
Driver/power unit/transformer	Power supply unit	
Driver included	Yes	
Optical cover/lens type	Polycarbonate bowl/cover	
Luminaire light beam spread	100° x 120°	
Control interface	-	
Connection	Connection unit 2-pole	
Protection class IEC	Safety class II	
Glow-wire test	Temperature 650 °C, duration 30 s	
Flammability mark	-	
CE mark	CE mark	
ENEC mark	-	
Warranty period	1 years	
Constant light output	No	
Number of products on MCB of 16 A type B -		
EU RoHS compliant	No	

Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.5
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Polypropylene
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Polypropylene
Optical cover/lens finish	Opal
Overall height	88 mm
Overall diameter	220 mm

## **Essential Smartbright Bulkhead**

Color	White
Approval and Application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK06 [ 1 J]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	1600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	80 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>70
Initial chromaticity	SDCM<6
Initial input power	20 W
Power consumption tolerance	+/-10%

20000 h


Application Conditions	
Ambient temperature range	-30 to +35 °C
Maximum dim level	Not applicable
Product Data	
Full product code	871016333530899
Order product name	WT045C LED20/NW PSU CFW L1665
EAN/UPC - Product	8710163335308
Order code	911401735862
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	911401735862
Net Weight (Piece)	0.300 kg

<sup>650°C</sup> IP 65 IK 06

## Over Time Performance (IEC Compliant)

Median useful life L70B50

### **Dimensional drawing**



WTOxxx



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.