

Eaton 9E1000I

Catalog Number: 9E1000I

Eaton 9E UPS, 1000 VA, 800 W, Input: C14, Output: (4) C13, Tower



Фото репрезентативне

General specifications

Product Name	Catalog Number
Eaton 9E UPS	9E1000I
UPC	Product Length/Depth
786689166564	356 mm
Product Height	Product Width
228 mm	144 mm
Product Weight	Warranty
22.1 kg	2 year
Compliances	Certifications
CE Marked	IEC/EN 62040-1
TUV	IEC/EN 62040-2
	CE
	EAC

Special features

Double conversion topology
Constantly monitors power conditions and regulates voltage and frequency
Internal bypass allows service continuity in case of UPS fault
LCD display for real-time status and measurements
Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)

Type

UPS

Topology

Online/Double-conversion

Form factor

Tower

Construction type

Free standing model

Color

Black

VA rating

1000 VA

Wattage

800 W

Rack mounting kit

No

Package contents

UPS
USB cable
Serial cable
Quickstart guide
Safety instructions

Internal bypass

Yes

Declarations of conformity

[EU Declaration of Conformity](#)

Hot swap power

No

Auto shutdown function

Yes

Primary frequency - max

70 Hz

Primary frequency - min

40 Hz

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input frequency range

40-70 Hz

Input power factor

>.99

Receptacle

(4) C13

Number of Outputs C13

4

Output waveform

Sine wave

Voltage

230V

Output nominal voltage

230V default (220/230/240V)

Feed type

1

Voltage type

AC

Runtime graph

\$row.attributeValue.cdata

Battery management

Automatic battery test

Deep discharge protection

Battery replacement

Replacable batteries

Battery rating

12 V / 9 Ah

Battery type

Sealed, lead-acid

Extended battery capability

Yes

Runtime at half load

11.5 min

Communication

USB port (HID compliant)

Serial port (RS232)

Communication slot

Expansion slots

One slot for optional communication card

Ethernet interface

No

Includes network card

No

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power
Protector

User interface

LCD Display

Type of interface

Other

Potential free switch contact

No

Altitude

3000 m

BTU Rating

Online: 300

Noise level

<37 dB at 1 meter

Relative humidity

0-95% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Input voltage - max

300 V

Input voltage - min

100 V

Output voltage - max

240 V

Output voltage - min

220 V

Secondary frequency - max

60 Hz

Secondary frequency - min

50 Hz

Battery quantity

2

Efficiency

91

Efficiency (eco-mode)

97

Input voltage range

176-300 V (100 V-300 V with derating)

Output frequency

50/60 Hz

Output power factor

0.8

Output voltage range

220/230/240 V +/- 2%

Phase (input)

1

Phase (output)

1

Runtime at full load

5 min

Voltage distortion output (linear load) - max



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Усі права захищені.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia