

LAS 40 3p COP



Specifications

ETI Code	004664203
Description	LAS 40 3p COP
Function	Manual change-over switches (1-0-2)
Rated current (A)	40
Type	DIN-rail mounted
No. Of poles	3
Catalogue Group	LAS COP
	0

Online product page 

Other documentation



Technical data catalogue

3D Model

CE declaration

ETIM international clasification

Classification	EC000216
Class name	Switch disconnecter
Version as main switch	
Version as maintenance-/service switch	
Version as safety switch	
Version as emergency stop installation	
Version as reversing switch	1
Max. rated operation voltage Ue AC	690V
Rated operating voltage	220...690V
Rated permanent current Iu	40A
Rated permanent current at AC-21, 400 V	40A
Rated operation power at AC-3, 400 V	15kW
Rated short-time withstand current Icw	3kA
Rated operation power at AC-23, 400 V	16kW
Switching power at 400 V	16kW
Conditioned rated short-circuit current Iq	10kA
Motor drive optional	
Motor drive integrated	
Voltage release optional	
Device construction	Built-in device fixed built-in technique
Suitable for ground mounting	1
Suitable for front mounting 4-hole	
Suitable for front mounting center	
Suitable for distribution board installation	1
Suitable for intermediate mounting	
Colour control element	Black
Type of control element	Short thumb-grip
Interlockable	
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP40

Dimension drawing

