

# PRODUCT FAMILY DATASHEET

## LED STRIP VALUE-300 PROTECTED

IP65 protected LED strips with 300 lm/m for general applications



---

### Areas of application

- General indoor illumination
- General outdoor illumination
- Decorative illumination
- Private living areas

---

### Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Suitable for use in damp conditions thanks to high type of protection
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

---

### Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 20,000 h at Tc max.: 65°C
- Luminous flux: 300 lm/m
- Color rendering index  $R_a$ : > 80
- Available with light color: Warm White, White, Daylight
- Type of protection: IP65
- Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)



TECHNICAL DATA

Electrical data

Product description	Nominal wattage	Nominal wattage per meter	Nominal voltage	Input voltage range	Reverse Voltage
LS VAL -300/830/5/IP65	14.50 W	3.0 W <sup>1)</sup>	24 V <sup>2)</sup>	23...25 V <sup>2)</sup>	25 V <sup>2)</sup>
LS VAL -300/865/5/IP65	14.50 W	3.0 W <sup>1)</sup>	24 V <sup>2)</sup>	23...25 V <sup>2)</sup>	25 V <sup>2)</sup>
LS VAL -300/840/5/IP65	14.50 W	3.0 W <sup>1)</sup>	24 V <sup>2)</sup>	23...25 V <sup>2)</sup>	25 V <sup>2)</sup>
LS VAL -300/827/5/IP65	14.50 W	3.0 W <sup>1)</sup>	24 V <sup>2)</sup>	23...25 V <sup>2)</sup>	25 V <sup>2)</sup>

Product description	Type of current	Nominal current
LS VAL -300/830/5/IP65	DC	542 mA
LS VAL -300/865/5/IP65	DC	542 mA
LS VAL -300/840/5/IP65	DC	542 mA
LS VAL -300/827/5/IP65	DC	542 mA

1) Value based on first meter of the product

2) V<sub>DC</sub>

Photometrical data

Product description	Total useful luminous flux [PICOS]	Luminous efficacy	Luminous flux	Luminous flux per meter	Luminous flux per module chain
LS VAL -300/830/5/IP65	295 lm	98 lm/W <sup>1)</sup>	1244 lm	295 lm <sup>1)</sup>	1244 lm
LS VAL -300/865/5/IP65	310 lm	103 lm/W <sup>1)</sup>	1315 lm	310 lm <sup>1)</sup>	1315 lm
LS VAL -300/840/5/IP65	310 lm	103 lm/W <sup>1)</sup>	1315 lm	310 lm <sup>1)</sup>	1315 lm
LS VAL -300/827/5/IP65	285 lm	95 lm/W <sup>1)</sup>	1200 lm	285 lm <sup>1)</sup>	1200 lm

Product description	Color temperature	Color rendering index Ra	Light color LED	Light color (designation)	Standard deviation of color matching
LS VAL -300/830/5/IP65	3000 K	> 80	White	White	≤6 sdc <sub>m</sub>
LS VAL -300/865/5/IP65	6500 K	> 80	Daylight	Cool Daylight	≤6 sdc <sub>m</sub>
LS VAL -300/840/5/IP65	4000 K	> 80	Cool white	Cool White	≤6 sdc <sub>m</sub>
LS VAL -300/827/5/IP65	2700 K	> 80	Warm white	Warm White	≤6 sdc <sub>m</sub>

1) Value based on first meter of the product

Light technical data



Product description	Beam angle	Rated beam angle (half peak value)
LS VAL -300/830/5/IP65	105 °	110.00 °
LS VAL -300/865/5/IP65	105 °	110.00 °
LS VAL -300/840/5/IP65	105 °	110.00 °
LS VAL -300/827/5/IP65	105 °	110.00 °

## LED MODULE INFORMATION

Product description	Number of LEDs per meter	Number of LEDs per module	Number of LEDs per smallest unit
LS VAL -300/830/5/IP65	60	300	6
LS VAL -300/865/5/IP65	60	300	6
LS VAL -300/840/5/IP65	60	300	6
LS VAL -300/827/5/IP65	60	300	6

## Dimensions &amp; weight

Product description	Length	Overall length	Length – smallest unit	Cable length
LS VAL -300/830/5/IP65	5000.00 mm	5000.00 mm	100.0 mm	500.000
LS VAL -300/865/5/IP65	5000.00 mm	5000.00 mm	100.0 mm	500.000
LS VAL -300/840/5/IP65	5000.00 mm	5000.00 mm	100.0 mm	500.000
LS VAL -300/827/5/IP65	5000.00 mm	5000.00 mm	100.0 mm	500.000

Product description	Width	Height	Prewired	Conductor cross section	LED pitch
LS VAL -300/830/5/IP65	10.00 mm	4.10 mm	Yes	0.5 mm <sup>2</sup>	16.67 mm
LS VAL -300/865/5/IP65	10.00 mm	4.10 mm	Yes	0.5 mm <sup>2</sup>	16.67 mm
LS VAL -300/840/5/IP65	10.00 mm	4.10 mm	Yes	0.5 mm <sup>2</sup>	16.67 mm
LS VAL -300/827/5/IP65	10.00 mm	4.10 mm	Yes	0.5 mm <sup>2</sup>	16.67 mm

Product description	Short pitch	Product weight
LS VAL -300/830/5/IP65	No	207.00 g
LS VAL -300/865/5/IP65	No	207.00 g
LS VAL -300/840/5/IP65	No	207.00 g
LS VAL -300/827/5/IP65	No	207.00 g

## Product line drawing





LS VAL -300/827/5/IP65

### Colors & materials

Product description	Cover material
LS VAL -300/830/5/IP65	Silicone
LS VAL -300/865/5/IP65	Silicone
LS VAL -300/840/5/IP65	Silicone
LS VAL -300/827/5/IP65	Silicone

### Temperatures & operating conditions

Product description	Ambient temperature range	Maximum temperature at tc test point	Temperature range in operation
LS VAL -300/830/5/IP65	-20...+40 °C <sup>1)</sup>	65 °C <sup>2)</sup>	-20...+65 °C <sup>3)</sup>
LS VAL -300/865/5/IP65	-20...+40 °C <sup>1)</sup>	65 °C <sup>2)</sup>	-20...+65 °C <sup>3)</sup>
LS VAL -300/840/5/IP65	-20...+40 °C <sup>1)</sup>	65 °C <sup>2)</sup>	-20...+65 °C <sup>3)</sup>
LS VAL -300/827/5/IP65	-20...+40 °C <sup>1)</sup>	65 °C <sup>2)</sup>	-20...+65 °C <sup>3)</sup>

- 1) Providing that temperature at T<sub>c</sub> point is below max value during operation
- 2) Exceeding the maximum specified ratings can reduce expected life time or destroy the LED strip
- 3) At the T<sub>c</sub> point

### Capabilities

Product description	Dimmable	Dimming interface	Lowest bending radius	Self-adhesive	Reverse polarity protection
LS VAL -300/830/5/IP65	Yes <sup>1)</sup>	PWM	30 mm	Yes	Yes <sup>2)</sup>
LS VAL -300/865/5/IP65	Yes <sup>1)</sup>	PWM	30 mm	Yes	Yes <sup>2)</sup>
LS VAL -300/840/5/IP65	Yes <sup>1)</sup>	PWM	30 mm	Yes	Yes <sup>2)</sup>
LS VAL -300/827/5/IP65	Yes <sup>1)</sup>	PWM	30 mm	Yes	Yes <sup>2)</sup>

- 1) Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)
- 2) Up to maximum 25 V<sub>DC</sub>

### Certificates & standards

Product description	Approval marks – approval	Standards	Type of protection	Energy consumption	Energy efficiency class
LS VAL -300/830/5/IP65	RoHS / CE / REACH	Acc. to IEC 62471 / Acc. to IEC 60598-1 / Acc. to EN 60529 / Acc. to EN 62031 / Acc. to EN 55015 / Acc. to EN 61547	IP65	3.30 kWh/1000h <sup>1)</sup>	A+
LS VAL -300/865/5/IP65	RoHS / CE / REACH	Acc. to IEC 62471 / Acc. to IEC 60598-1 / Acc. to EN 60529 / Acc. to EN 62031 / Acc. to EN 55015 / Acc. to EN 61547	IP65	3.30 kWh/1000h <sup>1)</sup>	A+
LS VAL -300/840/5/IP65	RoHS / CE / REACH	Acc. to IEC 62471 / Acc. to IEC 60598-1 / Acc. to EN 60529 / Acc. to EN 62031 / Acc. to EN 55015 / Acc. to EN 61547	IP65	3.30 kWh/1000h <sup>1)</sup>	A+
LS VAL -300/827/5/IP65	RoHS / CE / REACH	Acc. to IEC 62471 / Acc. to IEC 60598-1 / Acc. to EN 60529 / Acc. to EN 62031 / Acc. to EN 55015 / Acc. to EN 61547	IP65	3.30 kWh/1000h <sup>1)</sup>	A+

Product description	Salt mist resistance acc. IEC 60068-2-52	UV resistance acc. IEC 60068-2-5
LS VAL -300/830/5/IP65	No	Yes
LS VAL -300/865/5/IP65	No	Yes
LS VAL -300/840/5/IP65	No	Yes
LS VAL -300/827/5/IP65	No	Yes

<sup>1)</sup> Value based on first meter of the product

## LOGISTICAL DATA

Product description	Temperature range at storage
LS VAL -300/830/5/IP65	-20...+85 °C
LS VAL -300/865/5/IP65	-20...+85 °C
LS VAL -300/840/5/IP65	-20...+85 °C
LS VAL -300/827/5/IP65	-20...+85 °C

## EQUIPMENT / ACCESSORIES

– Endcaps have to be ordered separately

## APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

## ADDITIONAL PRODUCT INFORMATION

– All the technical parameters apply to the entire LED module. In view of the complex manufacturing process for light emitting diodes, the typical



values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.

- All LED strips have a self-adhesive tape on the reverse side. LED strips can be attached to suitable materials, e.g. aluminum profiles. The surface of the material must be free of grease, oil, silicone and dirt particles. The adhesive tape can be used only one time, if the LED strip will be removed from the mounting surface, there could be a damage of the LED strips and the mounting material. The surface temperature of the mounting material should be in the temperature range of 18°C...35°C. Complete adhesion takes up to 72 h.
- According IPC 6013C – Use A the LED strips are designed for static installation. Vibrations, respective torsion and elongation/compression must be considered.
- In a wide temperature range operation field (e.g. outdoor installation) and a LED strip length with more than 2m suitable mounting surface is required. To avoid stress due to mismatch in expansion of the different materials, there should be an extra thicker adhesive tape between LED strip and mounting surface. Additionally, the LED strip should have enough space for thermal expansion at higher temperatures.
- Compensation due to chemical corrosion is excluded. A suitable protection against corrosive agents such as moisture, condensation etc. must be provided. Hydrogen sulfide (H2S) will cause an accelerated corrosion which leads to shortened lifetime or premature failure.
- IP00 LED strips have not surface coating. Consequently, they have no protection against contact and corrosion.
- Installation of the LED strip has to be done by a qualified electrician.
- Handle with care to avoid mechanical product damage
- If the maximum operating and storage temperature ratings will be exceeded, the expected lifetime will be reduced or even the LED strip will be destroyed. It is not allowed to operate the LED strip over the specified Tc temperature (acc. EN 60598-1 under steady state conditions)
- It is not allowed to exceed the maximum operation voltage. This could cause a hazardous overload and will destroy the LED strip.
- The applicable electrical and safety standards have to be maintained for a LED strip installations
- Pay attention on correct polarity. Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Galvanic Insulation between LED strip and mounting surface must be ensured. This Insulation is needed especially in the area of connections or cut ends.
- In installations of LED strips ESD safety must be taken in account. Adequate precautions during installation and operation for the products are required.
- LED strip can be operated only by a SELV LED driver, which comply with the applicable lighting standards and fits to LED strips rating. A safety operation of the LED strips require a SELV LED driver with an electronically stabilized power supply protection against short circuits, overload and overheating.
- To avoid a damage of the LED strip, the unmounted LED strip should be handled and stored only in the original LEDVANCE packaging (wheel / ESD bag). Repacking is not allowed. Cutted IP 6x LED strips can be stored only with mounted endcaps.

## SALES AND TECHNICAL SUPPORT

Sales and Technical Support [www.ledvance.com](http://www.ledvance.com)

## COUNTRY SPECIFIC INFORMATION

Product description	Product code	METEL-Code	SEG number	STK number	UK Org
LS VAL -300/830/5/IP65	4058075296213	-	-	4246055	-
LS VAL -300/865/5/IP65	4058075296275	-	-	4246057	-
LS VAL -300/840/5/IP65	4058075296244	-	-	4246056	-
LS VAL -300/827/5/IP65	4058075296183	-	-	4246054	-

## DOWNLOAD DATA

DOWNLOAD DATA	
---------------	--



User instruction  
LED STRIP VALUE IP65



DOWNLOAD DATA	
	Certificates EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025
	Certificates RU C-DE.ML66.B.00889 29.06.2016-28.06.2021
	Declarations of conformity EU Declaration of conformity 3594030 LS VAL
	IES file (IES) LS VAL 300 830 5 IP65
	IES files (IES, additional) LS VAL-300-830-5-IP65-0.1M.
	LDT file (Eulumdat) LS VAL 300 830 5 IP65
	LDT files (Eulumdat, additional) LS VAL-300-830-5-IP65-0.1M
	Catalogs LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)
	User instruction LED STRIP VALUE IP65
	Certificates EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025
	Certificates RU C-DE.ML66.B.00889 29.06.2016-28.06.2021
	Declarations of conformity EU Declaration of conformity 3594030 LS VAL
	IES file (IES) LS VAL 300 865 5 IP65
	IES files (IES, additional) LS VAL-300-865-5-IP65-0.1M
	LDT file (Eulumdat) LS VAL 300 865 5 IP65
	LDT files (Eulumdat, additional) LS VAL-300-865-5-IP65-0.1M
	Catalogs LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)
	User instruction LED STRIP VALUE IP65



**DOWNLOAD DATA**

	Certificates EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025
	Certificates RU C-DE.ML66.B.00889 29.06.2016-28.06.2021
	Declarations of conformity EU Declaration of conformity 3594030 LS VAL
	IES file (IES) LS VAL 300 840 5 IP65
	IES files (IES, additional) LS VAL-300-840-5-IP65-0.1M
	LDT file (Eulumdat) LS VAL 300 840 5 IP65
	LDT files (Eulumdat, additional) LS VAL-300-840-5-IP65-0.1M
	Catalogs LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)
	User instruction LED STRIP VALUE IP65
	Certificates EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025
	Certificates RU C-DE.ML66.B.00889 29.06.2016-28.06.2021
	Declarations of conformity EU Declaration of conformity 3594030 LS VAL
	IES file (IES) LS VAL 300 827 5 IP65
	IES files (IES, additional) LS VAL-300-827-5-IP65-0.1M
	LDT file (Eulumdat) LS VAL 300 827 5 IP65
	LDT files (Eulumdat, additional) LS VAL-300-827-5-IP65-0.1M
	Catalogs LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)

**LOGISTICAL DATA**





Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075296213	Folding box 1	262 mm x 262 mm x 30 mm	447.00 g	2.06 dm <sup>3</sup>
4058075296275	Folding box 1	262 mm x 262 mm x 30 mm	447.00 g	2.06 dm <sup>3</sup>
4058075296244	Folding box 1	262 mm x 262 mm x 30 mm	447.00 g	2.06 dm <sup>3</sup>
4058075296183	Folding box 1	262 mm x 262 mm x 30 mm	447.00 g	2.06 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### ACCESSORIES MANDATORY

Product description	Accessory name	Accessory code
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS VAL -300/830/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075239913
LS VAL -300/830/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -30/220-240/24/P	▶ 4058075239890
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS VAL -300/830/5/IP65	LED DRIVER VALUE -30/220-240/24	▶ 4058075240056
LS VAL -300/830/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075379190
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -40/220-240/24/P	▶ 4058075379176
LS VAL -300/830/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS VAL -300/830/5/IP65	LED DRIVER VALUE -60/220-240/24	▶ 4058075240094
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS VAL -300/830/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -20/220-240/24/P	▶ 4058075239951
LS VAL -300/830/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS VAL -300/830/5/IP65	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS VAL -300/830/5/IP65	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -10/SMB	▶ 4058075275676
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -CP/P2/500/P	▶ 4058075272958
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -CSD/P2/P	▶ 4058075275485
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -CSW/P2/50/P	▶ 4058075273245
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/865/5/IP65	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS VAL -300/865/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -30/220-240/24/P	▶ 4058075239890



Product description	Accessory name	Accessory code
LS VAL -300/865/5/IP65	LED DRIVER VALUE -30/220-240/24	▶ 4058075240056
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -20/220-240/24/P	▶ 4058075239951
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -40/220-240/24/P	▶ 4058075379176
LS VAL -300/865/5/IP65	LED DRIVER VALUE -60/220-240/24	▶ 4058075240094
LS VAL -300/865/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS VAL -300/865/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075379190
LS VAL -300/865/5/IP65	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS VAL -300/865/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS VAL -300/865/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS VAL -300/865/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075239913
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -10/SMB	▶ 4058075275676
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -CP/P2/500/P	▶ 4058075272958
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -CSD/P2/P	▶ 4058075275485
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -CSW/P2/50/P	▶ 4058075273245
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -40/220-240/24/P	▶ 4058075379176
LS VAL -300/840/5/IP65	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS VAL -300/840/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -30/220-240/24/P	▶ 4058075239890
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS VAL -300/840/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS VAL -300/840/5/IP65	LED DRIVER VALUE -60/220-240/24	▶ 4058075240094
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075379190
LS VAL -300/840/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075239913
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -20/220-240/24/P	▶ 4058075239951
LS VAL -300/840/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS VAL -300/840/5/IP65	LED DRIVER VALUE -30/220-240/24	▶ 4058075240056
LS VAL -300/840/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS VAL -300/840/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS VAL -300/840/5/IP65	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -10/SMB	▶ 4058075275676
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -CP/P2/500/P	▶ 4058075272958
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -CSD/P2/P	▶ 4058075275485



Product description	Accessory name	Accessory code
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -CSW/P2/50/P	▶ 4058075273245
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/827/5/IP65	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS VAL -300/827/5/IP65	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS VAL -300/827/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075379190
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS VAL -300/827/5/IP65	LED DRIVER VALUE -60/220-240/24	▶ 4058075240094
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -40/220-240/24/P	▶ 4058075379176
LS VAL -300/827/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -20/220-240/24/P	▶ 4058075239951
LS VAL -300/827/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS VAL -300/827/5/IP65	LED DRIVER VALUE -30/220-240/24	▶ 4058075240056
LS VAL -300/827/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -60/220-240/24/P	▶ 4058075239913
LS VAL -300/827/5/IP65	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS VAL -300/827/5/IP65	LED DRIVER OUTDOOR PERFORMANCE -30/220-240/24/P	▶ 4058075239890
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -10/SMB	▶ 4058075275676
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -CP/P2/500/P	▶ 4058075272958
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -CSD/P2/P	▶ 4058075275485
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -CSW/P2/50/P	▶ 4058075273245
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744

**ACCESSORIES OPTIONAL**

Product description	Accessory name	Accessory code
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/1	▶ 4058075278134
LS VAL -300/830/5/IP65	LED Strip Profiles Medium -PM04/UW/23X15,5/10/1	▶ 4058075278400
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/2	▶ 4058075401440
LS VAL -300/830/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/1	▶ 4058075278103
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/2	▶ 4058075401471
LS VAL -300/830/5/IP65	LED Strip Profiles Medium -PM06/E/18X18/12/1	▶ 4058075279308
LS VAL -300/830/5/IP65	LED Strip Profiles Medium -PM05/U/17,5X14,5/10/1	▶ 4058075279278
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/2	▶ 4058075401501



Product description	Accessory name	Accessory code
LS VAL -300/830/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/1	▶ 4058075278165
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/1	▶ 4058075278165
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/1	▶ 4058075278134
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/2	▶ 4058075401501
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/2	▶ 4058075401440
LS VAL -300/865/5/IP65	LED Strip Profiles Medium -PM06/E/18X18/12/1	▶ 4058075279308
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/2	▶ 4058075401471
LS VAL -300/865/5/IP65	LED Strip Profiles Medium -PM04/UW/23X15,5/10/1	▶ 4058075278400
LS VAL -300/865/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/1	▶ 4058075278103
LS VAL -300/865/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/865/5/IP65	LED Strip Profiles Medium -PM05/U/17,5X14,5/10/1	▶ 4058075279278
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/2	▶ 4058075401440
LS VAL -300/840/5/IP65	LED Strip Profiles Medium -PM06/E/18X18/12/1	▶ 4058075279308
LS VAL -300/840/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/1	▶ 4058075278103
LS VAL -300/840/5/IP65	LED Strip Profiles Medium -PM04/UW/23X15,5/10/1	▶ 4058075278400
LS VAL -300/840/5/IP65	LED Strip Profiles Medium -PM05/U/17,5X14,5/10/1	▶ 4058075279278
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/1	▶ 4058075278134
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/1	▶ 4058075278165
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/2	▶ 4058075401471
LS VAL -300/840/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/2	▶ 4058075401501
LS VAL -300/827/5/IP65	LED Strip Profiles Medium -PM06/E/18X18/12/1	▶ 4058075279308
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/2	▶ 4058075401501
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/1	▶ 4058075278134
LS VAL -300/827/5/IP65	LED Strip Performance Connectors -10/SE/P SIL-SEAL	▶ 4058075275744
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW03/U/26X26/14/1	▶ 4058075278165
LS VAL -300/827/5/IP65	LED Strip Profiles Medium -PM04/UW/23X15,5/10/1	▶ 4058075278400
LS VAL -300/827/5/IP65	LED Strip Profiles Medium -PM05/U/17,5X14,5/10/1	▶ 4058075279278
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW02/UW/39X26/14/2	▶ 4058075401471
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/1	▶ 4058075278103
LS VAL -300/827/5/IP65	LED Strip Profiles Wide -PW01/U/26X8/14/2	▶ 4058075401440

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

