

WVB 18 LT BL 11-125 Quick (613057660) Cordless angle grinder 18V 2x5.5Ah LiHD; Charger ASC 145; metaBOX 165 L

Order no. 613057660 EAN 4061792206618



Product may differ from Image



- Brushless cordless angle grinder of the new generation: as powerful as a 1,100 Watt mains-powered tool thanks to 40% more power
- Service-free Brushless motor with highest efficiency and maximum handiness
- Variable speed setting with thumbwheel for working on materials requiring customised speeds, and at speeds which remain constant under load
- Fast brake system for highest user safety: Disc stops within 1 second after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com



Technical data

Characteristics

| Type of battery pack | LiHD |
|---|--|
| Battery pack capacity | 2 x 5.5 Ah |
| Battery voltage | 18 V |
| Disc-Ø | 125 mm / 5 " |
| Max. cutting depth | 33 mm / 1.299 " |
| No-load speed | 2800 - 10000 rpm |
| Spindle thread | M 14 |
| Handle circumference | 191 mm / 7.52 " |
| Weight without battery pack | 1.8 |
| Weight with battery pack | 2.8 |
| | |
| Vibration | |
| Vibration Surface grinding | 8 m/s ² |
| | 8 m/s ² 1.5 m/s ² |
| Surface grinding | |
| Surface grinding Uncertainty of measurement K | 1.5 m/s ² |
| Surface grinding Uncertainty of measurement K Grinding with sandpaper | 1.5 m/s ² 2.5 m/s ² |
| Surface grinding Uncertainty of measurement K Grinding with sandpaper Uncertainty of measurement K | 1.5 m/s ² 2.5 m/s ² |
| Surface grinding Uncertainty of measurement K Grinding with sandpaper Uncertainty of measurement K Noise emission | 1.5 m/s ² 2.5 m/s ² 1.5 m/s ² |

Scope of delivery

Guard Side handle Dust protection filter 2 LiHD battery packs (18 V/5.5 Ah) Quick charger ASC 145 "AIR COOLED" metaBOX 165 L Inner support flange M-Quick flange nut