

PRODUCT DATASHEET SMART+ WiFi Candle 40 4.9 W/2700...6500 K E14

SMART+ WiFi Candle Multicolour | Classic candle shape with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h





TECHNICAL DATA

Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	230 V
Nominal current	45 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.5
Claimed equiv. conventional lamp power	40 W

Photometrical data


Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	95 lm/W
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



Light technical data

Beam angle	200 °
Starting time	< 0.5 s

Dimensions & Weight



Product weight	32.00 g
Diameter	37.50 mm
Length	107.00 mm
Width (incl. round luminaires)	37.50 mm
Height (incl. round luminaires)	37.50 mm
Outer bulb [PICOS]	B40

Lifespan

Nominal lamp life time	20000 h
Lumen maintenance at end of serv	0.70

Colors & materials

Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Ambient temperature range	20* 10 C

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E14

Capabilities

Dimmable	Yes
----------	-----

Compatible smart home technology Google Assistant / Amazon Alexa		
Certificates & Standards		
Energy efficiency class	F ¹⁾	
Energy consumption	5.00 kWh/1000h	
Standards	CE	
Type of protection	IP20	

 $^{1) \ {\}sf Energy} \ {\sf efficiency} \ {\sf class} \ ({\sf EEC}) \ {\sf on} \ {\sf a} \ {\sf scale} \ {\sf of} \ {\sf A} \ ({\sf highest} \ {\sf efficiency}) \ {\sf to} \ {\sf G} \ ({\sf lowest} \ {\sf efficiency})$

Energy labellling regulation data acc EU 2019/2015

NDLS
MLS
E14
yes
yes
No No
No
No
RANGE
0.50
0.50
Yes
0.463
0.420
0.00
SPHERE_360
0,9
0.50
not applicable
528208
AC33921

DOWNLOAD DATA

DOWNLOAD DATA



Installation guide

SMART+ WIFI INSTALLATION GUIDE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485570	Folding box 1	61 mm x 96 mm x 154 mm	103.00 g	0.90 dm³
4058075485587	Shipping box 4	210 mm x 165 mm x 135 mm	534.00 g	4.68 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.