

SSD | MP33 PR0 M.2 PCIe Gen3

TEAMGROUP MP33 PR0 M.2 PCIe SSD uses M.2 2280 specification and PCIe Gen3x4 interface. With the highest read/write speed of 2,100/1,700 MB/s^[1], once you've used it you will never go back. At the same time, it supports smart algorithm management mechanism that provides both efficiency and security. In addition, the five year warranty gives you peace of mind. MP33 PR0 will be your best choice of getting a M.2 PICe SSD.

Main Feature

- Once you've used the high speed PCIe, you will never go back
- High speed reading and writing for more efficiency
- Stable and durable- Not only fast, but reliable
- \cdot Up to 2TB of storage capacity
- Five year warranty providing customers with peace of mind

Ordering Information

Capacity	Team P/N
512GB	TM8FPD512G0C101
1TB	TM8FPD001T0C101
2TB	TM8FPD002T0C101



Specification

Interface	PCIe 3.0 x4 with NVMe 1.3
Capacity	512GB / 1TB / 2TB ^[2]
Color	Blue / Black
Voltage	DC +3.3V
Operation Temperature	0°C ~ 70°C
Storage Temperature	-40°C ~ 85°C
Terabyte Written	512GB / >400TB 1TB / >600TB 2TB / >1,000TB ^[3]
Performance	Crystal Disk Mark: Read/Write: up to 2,100/1,700 MB/s ^[1]
	IOPS: Read/Write: 220K/200K IOPS Max ^[1]
Weight	6g
Dimensions	80(L) x 22(W) x 3.8(H) mm
Humidity	RH 90% under 40°C (operational)
Vibration	80Hz~2,000Hz/20G
Shock	1,500G/0.5ms
MTBF	2,000,000 hours
Operating System	System Requirements: • Windows 10 / 8.1 / 8 / 7 ^[4] • Linux 2.6.33 or later
Warranty	5-year limited warranty

[1] Transmission speed will vary according to different hardware/software conditions, therefore the data can only use for basic reference.

[2] 1GB=1,000,000,000 Bytes. In OS system, it would be displayed as 1,000,000 Bytes/1024/1024/1024 = 0.93GB

[3] Definition and conditions of TBW (Terabytes Written)are based on JEDEC standard

[4] PCIe SSD works best under WIN8.1 and WIN10 operating system. Windows Operating Systems earlier than Windows 8.1 does not support NVMe Driver natively. Users will need to install NVMe Driver prior installing the SSD.

We reserve the right to modify product specifications without prior notice.

Tel: +886-2-82265000 Fax: +886-2-82265808 mail: sales@teamgroup.com.tw / rma@teamgroup.com.tw