

# PRODUCT DATASHEET ENDURA STYLE Sphere 8 W DG

ENDURA® STYLE SPHERE | Spotlights with rotatable head, round shape



## Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

### **Product benefits**

- Energy-efficient thanks to LED technology
- Easy and quick installation

#### **Product features**

- Bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Adjustable modules: rotation angle 180°



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	8.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Nominal current	65 mA
Power factor $\lambda$	> 0,5

### Photometrical data

Color temperature	3000 K
Luminous flux	600 lm
Luminous efficacy	75 lm/W
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm
Color rendering index Ra	> 80

# Light technical data

Beam angle	170 °

# Dimensions & weight



Length	105.00 mm
Height	89.00 mm
Width	114.00 mm
Product weight	500.000 g

# Colors & materials

Body material	Aluminum
Product color	Dark gray
Housing color	Dark gray
Cover material	Polycarbonate (PC)

# Temperatures & operating conditions

15000
30000 h
-

# Additional product data

Mounting location	Wall

# **Capabilities**

Dimmable	No
Type of connection	Screw terminal
ErP LEDmod replaceable	Not replaceable

## Certificates & standards

Protection class	1
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

# **LOGISTICAL DATA**

Temperature range at storage -20+85 °C	
--	--

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction ENDURA® STYLE SPHERE HEMISPHERE
	Tender documents Tender Text 4058075216624
PDF	Packaging insert Legal insert C Outdoor - Not dimmable

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075216624	Folding box 1	124 mm x 154 mm x 166 mm	540.00 g	3.17 dm <sup>3</sup>
4058075216631	Shipping box 6	385 mm x 170 mm x 355 mm	3472.00 g	23.23 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.