

Xerox[®] WorkCentre[®] 6515 Color Multifunction Printer



| System Specifications | WorkCentre® 6515 | |
|---|--|--|
| One-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm | Up to 30 ppm color and black-and-white Up to 28 ppm color and black-and-white Up to 24 ppm color and black-and-white | |
| Two-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm | Up to 19 ppm color and black-and-white Up to 18 ppm color and black-and-white Up to 17 ppm color and black-and-white | |
| Monthly Duty Cycle ¹ | Up to 50,000 pages / month | |
| Recommended Average Monthly Print Volume ² | Up to 3,000 pages | |
| Processor | 1.05 GHz | |
| Memory | 2 GB | |
| Connectivity | 10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct [®] | |
| Device Specifications | | |
| Electrical Requirements | | |
| North America | Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A | |
| Europe | Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A | |
| Power Consumption | | |
| Operation ⁴ | 120V: Maximum 350 watts 220V: Maximum 370 watts | |
| Standby Mode ⁴ | 120V: Maximum 51 watts 220V: Maximum 52 watts | |
| Power Off Mode ⁴ | 120V: Maximum 0.2 watts 220V: Maximum 0.3 watts | |
| Sleep Mode ⁴ | 120V: Maximum 1.1 watts 220V: Maximum 1.2 watts | |
| Warm-up (from Sleep Mode) | As fast as 27 seconds | |

| Operating Environment | | | | |
|---|--|-------------------|-------------------|--------------------|
| Required Temperature Range (Storage) | -4°F to 104°F / -20°C to 40°C | | | |
| Required Temperature Range (Operating) | 41°F to 90°F / 5°C to 32°C | | | |
| Required Relative Humidity | 15% to 85% | | | |
| Sound Power Levels | Operating: 6.84 B or less Standby: 4.25 B or less | | | |
| Sound Pressure Levels | Operating: 52.5 dB(A) or less Standby: 26.3 dB(A) or less | | | |
| Dimensions and Weights (unpackaged) | Width | Depth | Height | Weight |
| WorkCentre® 6515 | 16.5 in. / 420 mm | 19.9 in. / 506 mm | 19.7 in. / 500 mm | 67.7 lb. / 30.7 kg |
| 550-sheet Paper Tray | 16.5 in. / 420 mm | 18.3 in. / 465 mm | 5.9 in. / 150 mm | 14.8 lb. / 6.7 kg |
| Dimensions and Weights (packaged) | Width | Depth | Height | Weight |
| WorkCentre® 6515 | 25 in. / 634 mm | 22.8 in. / 580 mm | 26 in. / 659 mm | 79.8 lb. / 36.2 kg |
| 550-sheet Paper Tray | 21.1 in. / 535 mm | 23 in. / 584 mm | 9.8 in. / 248 mm | 18.7 lb. / 8.5 kg |
| Certifications | | | | |

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

| Print | | |
|---|---|--|
| First-Print-Out Time | As fast as 12 seconds color and black-and-white | |
| | | |
| Print Resolution | Up to 1200 x 2400 dpi | |
| Page Description Languages | Adobe® PostScript® 3™ | |
| | PCL® 5e, 6 PDF | |
| | TIFF | |
| Maximum Print Area | 4 mm edge of paper | |
| Print Features | Banner Sheets | |
| | Booklet Print | |
| | Cover / Separators | |
| | Draft Mode | |
| | Fit to Page | |
| | N-up | |
| | Overlays PANTONE® Color Calibrated Solid-color Simulations | |
| | PANTONE' Color Calibrated Solid-color Simulations Personal Print | |
| | Proof Print | |
| RAM Collation | | |
| | Run Black | |
| | Saved Print | |
| | Secure Print | |
| | Watermarks | |
| Print from USB Allows walk-up printing from Type A USB port | | |
| | Supports direct printing from computer via Type B USB port | |
| | Supported file formats: PDF, JPEG, TIFF, XPS | |
| Operating Systems | Windows [®] 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 | |
| | Mac OS® version 10.10 and higher | |
| | Citrix® | |
| | Redhat® Enterprise | |
| | Linux [®] IBM [®] AIX [®] 5 | |
| | HP-UX® 11iv2 | |
| | Oracle® Solaris 9, 10 | |
| | Fedora Core 12-15 | |
| | SUSE® | |
| | 1 3032 | |

| Font Canability | 136 PartScript fonts | |
|---|---|--|
| Font Capability | 136 PostScript fonts 88 PCL fonts | |
| Xerox [®] Mobile Express Driver [®] | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver® automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. | |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. | |
| Сору | | |
| Document Scanner | Single-pass Duplex Automatic Document Feeder (DADF) with 50-sheet capacity | |
| Document Scanner Size | Platen: Up to 8.5 x 11.7 in / A4 DADF: 8.5 x 14 in. / 216 x 356 mm | |
| Simplex Speed | Black-and-white: Up to 21 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 13 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm | |
| Duplex Speed | Black-and-white: Up to 9 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 8 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm | |
| First-Copy-Out Time | As fast as 12 seconds from the platen | |
| Sides (input: output) | 1:1, 1:2, 2:2, and 2:1 | |
| Quantity | 1 to 999 | |
| Resolution | Up to 600 x 600 dpi | |
| Reduction / Enlargement | Variable zoom from 25 % to 400 % in 1 % increments | |
| Concurrency | Concurrent scanning and printing | |
| Copy Features | Automatic Background Suppression Book Copying Book Copying with Center Erase Collation Darkness Control Edge Erase ID Card Copy Image Shift N-up Original Type Reduce/Enlarge (25 % -400 %) Sample Copy Sharpness | |
| Scan | | |
| Capability | Color and black-and-white | |
| Concurrency | Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs | |
| Input Speed – Black-and-White | Scan up to 37 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm | |
| Input Speed – Color | Scan up to 21 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm | |
| Resolution | Optical – 600 x 600 dpi | |
| Bit Depth | 24-bit Color / 8-bit Grayscale | |
| Maximum Scan Area | Platen: Up to 8.5 x 11.7 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm | |
| Network Filing Protocol | FTP SMTP SMB | |

| File Formats | JPG Single-page and Multi-page TIFF PDF Searchable PDF with integrated OCR | |
|--|---|--|
| Scan Driver Compatibility | WIA TWAIN | |
| Supported Scan Destinations | Scan to Email (local address book or LDAP integration) Scan to Network (via FTP/SMB) Scan to USB Memory Device Scan to Email (SMTP) Scan to WSD Scan to Application (TWAIN Network) Scan to WIA (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to Network Computer (SMB/FTP) Scan to Multiple Destinations in a Single Scan Job | |
| Fax ⁵ | | |
| Fax Speed | 33.6 Kbps | |
| Memory | 4 MB | |
| Resolution | Up to 400 x 400 dpi | |
| Compression | MH/MR/MMR/JBIG | |
| Fax Features | Broadcast Sending (up to 200 destinations) Delayed Start (up to 24 hours) Fax Address Book (up to 200 speed dials) Fax Forward to Email Fax Forwarding and Local Print Polling Receive Reject Junk Fax Secure Fax Receive | |
| Mobile Solutions and Mobile Devi | ce Apps | |
| Apple [®] AirPrint [®] | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. | |
| Google Cloud Print™ | Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device. | |
| Mopriα [®] Certified | Mopria [®] certification ensures you can print wirelessly from your Mopria [®] supported (Android) smart phone, tablet and other mobile devices instantly and easily. | |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. | |
| Xerox [®] Mobile Link App (Free at Google Play™ Store and Apple [®] App Store) | The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer. | |
| Xerox® Workplace Suite and Xerox® Workplace Cloud | Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security — for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow. • Xerox® Workplace Suite: On-site, your server • Xerox® Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.com/Mobility. | |

| Security | |
|---------------------------------------|---|
| Security Features | Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print Secure Fax Receive SNMP v3 LDAP (SASL) Network Authentication (Unix / Linux / Windows ADS) |
| Paper Handling | |
| Document Feeder | |
| Capacity ³ | Single-pass Duplex Automatic Document Feeder (DADF): 50 sheets |
| Sizes | Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm |
| bights | 16 lb. bond to 45 lb. cover / 60 to 125 gsm |
| Bypass Tray | |
| Capacity ³ | 50 sheets |
| Sizes | Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm |
| Weights | 16 lb. bond to 58 lb. cover / 60 to 220 gsm |
| Types | Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled |
| Tray 1 | |
| Capacity ³ | 250 sheets |
| Sizes | Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm 16 lb. bond to 65 lb. cover / 60 to 176 qsm |
| Weights Types | Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled |
| Optional Tray 2 Capacity ³ | 550 sheets |
| Sizes | Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm |
| Weights | 16 lb. bond to 65 lb. cover / 60 to 176 gsm |

| Types | Bond | |
|---------------------------------------|--|--|
| | Plain | |
| | Cardstock | |
| | Custom | |
| | Glossy Cardstock Hole Punched | |
| | | |
| | Letterhead | |
| | Lightweight Cardstock | |
| | Lightweight Glossy Cardstock | |
| | Preprinted | |
| | Recycled | |
| Total Capacity | | |
| Device Standard Capacity ³ | 300 sheets | |
| Device Total Capacity ³ | 850 sheets | |
| Paper Output | | |
| Output Capacity ³ | 150 sheets | |
| Automatic 2-Sided | Standard | |
| Device Management | | |
| Device Management | | |
| Network Protocols | TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD | |
| | SMB | |
| | SMTP, Secure SMTP | |
| | LDAP, Secure LDAP | |
| | Bonjour® / AirPrint® | |
| | FTP | |
| | Most protocols not in use can be disabled | |
| Administrative Protocols | DHCP, SNMP v2/3, WINS, DHCP Autonet, TLS, SNTP, MDNS | |
| Xerox® CentreWare® Web | | |
| | | |
| | A web-based server application for network administrators that permits web browser-based device A web-based server application for network administrators that permits web browser-based device A web-based server application for network administrators and INIX as a server the server application. | |
| | management from any workstation, whether running Windows or UNIX or any other operating | |
| | system Works with any SNMD managed printer from any manufacturer | |
| | Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device | |
| | upgrades, as well as basic accounting and asset management | |
| | | |
| Xerox® Embedded Web Server - | Integrated Device Web Page | |
| Device Status | Tray Status / Contents | |
| | Consumables Status | |
| | Billing / Usage | |
| | Quick Links | |
| Job Submission | Print-ready files (PS, PCL®, PDF, XPS, JPEG) | |
| | | |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device. | |
| Browsers | Microsoft [®] Internet Explorer | |
| | Microsoft Edge™_ | |
| | Mozilla™ Firefox [®] | |
| | Apple® Safari® | |
| | Google Chrome™ | |
| Remote Print Services | | |
| Xerox® Automated Meter | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® | |
| Readings (AMR) | device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter | |
| Neudings (Alvik) | reads are submitted to Xerox on time. | |
| | | |
| Xerox® Automatic Supplies | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to | |
| Replenishment (ASR) | manually manage supplies inventory. | |
| Troubleshooting and | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the | |
| Diagnostic Support | troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved | |
| Diagnostic Support | faster with increased uptime. | |
| | race, marmereased apartie. | |

| What's In The Box | |
|-------------------|--|
| | WorkCentre® 6515 Color Multifunction Printer Standard Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 1,000 print capacity⁶; Black: 1,500 print capacity⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord |

| Supplies and Accessories | Quantity | Part Number |
|---|--|--|
| Supplies | | |
| Extra-High Capacity Print Cartridges | Cyan: 4,300 standard pages ⁶ Magenta: 4,300 standard pages ⁶ Yellow: 4,300 standard pages ⁶ | 106R03690 106R03691 106R03692 |
| High Capacity Print Cartridges | Black 5,500 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶ | 106R03480 106R03477 106R03478 106R03479 |
| Standard Capacity Print Cartridges | Black: 2,500 standard pages ⁶ Cyan: 1,000 standard pages ⁶ Magenta: 1,000 standard pages ⁶ Yellow: 1,000 standard pages ⁶ | 106R03476 106R03473 106R03474 106R03475 |
| Drum Cartridges | Black: 48,000 pages ⁷ Cyan: 48,000 pages ⁷ Magenta: 48,000 pages ⁷ Yellow: 48,000 pages ⁷ | 108R01420 108R01417 108R01418 108R01419 |
| Waste Cartridge | 30,000 pages ⁷ | 108R01416 |
| Accessories | | |
| 550-sheet Paper Tray | | 097S04765 |
| Wireless Network Adapter | | 497K16750 |
| Cabinet (includes Caster Base) | | 097S04994 |

 $^{^{\}rm 1}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com.



² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print
 Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.