

R 20-20 230V



Specifications

ETI Code	002461210
Description	R 20-20 230V
Class name	Modular contactor
Type	AC
Size	2p, 1-module
Rated Frequency (Hz)	50/60
No. of NO contacts	2
Rated operational current I _e AC-1/AC-7 (A)	20
Rated operational voltage (V AC)	250
Rated control circuit voltage U _c (V AC)	230
0	

[Online product page](#)

Other documentation



[Technical data catalogue](#)

[3D Model](#)

[CE declaration](#)

[Eplan file](#)

ETIM international clasification

Classification	EC001653
Class name	Installation contactor for distribution board
Number of normally open contacts	2
Frequency	50/60
Construction size	2p, 1-module
Rated operating voltage	230...400V
Rated operation current	20A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	2
Max. incandescent lamp load	2160W
Max. load fluorescent lamp	935VA
Max. load fluorescent lamp (Duo circuit)	2320VA
Max. load fluorescent lamp (parallel compensated)	1020VA
Slider for hand switch	
Number of modular spacings	1
Built-in depth	60mm
Additional equipment possible	
Degree of protection (IP)	IP20

Dimension drawing

R20
165,150

